


BRASS SOLENOID VALVE 44









- Coil size 25mm
- 2/2 way NC - Direct acting
- Cold / high temperature fluids
- Multi purpose usage
- ED 100%

Technical data		
Body material	Brass	
Seal material	EPDM	
Tube material	Brass	
Working fluids	Air, water, steam	
Electrical connect.	6,3 x 0,8 fast-on terminal	
Insulation class	H	
220-230VAC 50-60Hz Approvals: CE; VDE	Power (VA)	9
	Amb. T. (°C)	120
	Fluid T. (°C)	150
100-120VAC 60Hz Approvals: CE; UL		

Performance					
Pipes INLET	Orifice Ø mm	Flow m3/h	MOPD (bar)		
			AC	AC	
1/8"	1,5	0,065	17	8	
1/8"	2,0	0,090	13	7	
1/8"	2,5	0,150	9	2	
1/8"	2,7	0,160	8	2	
1/8"	3,0	0,175	5	1	
1/8"	3,3	0,190	4	1	

Hydraulic connection


IN 1/8" – OUT 1/8"	IN 1/8" – OUT HOSE BIB	IN 1/8" – OUT HOSE BIB	IN 1/8" – OUT HOSE BIB	IN 1/8" – OUT HOSE BIB With safety v. Series 4413
<p>Series 4410</p> 	<p>Series 4425</p> 	<p>Series 4424</p> 	<p>Series 4423</p> 	
<p>IN 1/8" – OUT HOSE BIB Series 4422</p> 				

Notes


Food grade nickel treatment available on demand

Availability coil orientation


"A" (STANDARD)



"B"



"C"



"D"

