

EDT Series 2/2 Solenoid Valve(Normal Close)

Very low
working temperature
to High temperature



EDT-08E2-2LF

EDT	--	06	--	E1	--	1.5L	--	<input type="checkbox"/>
EDT series		Port size 06: 1/8" 08: 1/4" 10: 3/8" 15: 1/2"		Voltage E1: AC110V E2: AC220V E3: AC380V E4: DC24V E5: DC12V		Orifice 1.5L: 1,5mm 2L: 2mm 2.5L: 2,5mm 3L: 3mm 4L: 4mm 5L: 5mm 6L: 6mm		Blank: DIN connector F: flying leads

Specifications

Port size	Orifice	CV	Pressure difference(Bar)		Max temperature		Power	Model	Main Dimensions	
			Min	Max (air,inert gas)		Low temperature				Steam
				Low temperature	Steam					
1/8"	1.5	0.08	0	50	30	-100°C-- -10°C 99°C-- 200°C	AC27VA (16W) DC: 24W	EDT-06E2-1.5L	72*50*104	
1/8"	2	0.14		30	20			EDT-06E2-2L	72*50*104	
1/8"	2.5	0.23		17	17			EDT-06E2-2.5L	72*50*104	
1/8"	3	0.3		13	13			EDT-06E2-3L	72*50*104	
1/8"	4	0.6		7	7			EDT-06E2-4L	72*50*104	
1/4"	1.5	0.08		50	30			EDT-08E2-1.5L	72*50*104	
1/4"	2	0.14		30	20			EDT-08E2-2L	72*50*104	
1/4"	2.5	0.23		17	17			EDT-08E2-2.5L	72*50*104	
1/4"	3	0.3		13	13			EDT-08E2-3L	72*50*104	
1/4"	4	0.6		7	7			EDT-08E2-4L	72*50*104	
3/8"	5	0.65		5	5			EDT-10E2-5L	72*50*104	
3/8"	6	0.8		4	4			EDT-10E2-6L	72*50*104	
1/2"	5	0.65		5	5			EDT-15E2-5L	72*50*104	
1/2"	6	0.8		4	4			EDT-15E2-6L	72*50*104	