

# UW Series 2/2 Solenoid Valve(Normal Close)



## UW

2/2 Solenoid Valve ( N.C. )



### How to Order?

Series No.	Port Size	Voltage	Connection Type	Cover Color	Seal Material	Thread Type
UW	10: 3/8 " 15: 1/2 " 20: 3/4 " 25: 1 " 35: 1-1/4 " 40: 1-1/2 " 50: 2 "	E1: AC110V E2: AC220V E4: DC24V E5: DC12V E7: AC24V	Blank: DIN connector	Blank: Black	Blank: NBR E: EPDM V: VITON	Blank: G P: PT T: NPT

#### Order Example:

UW series solenoid valve, Brass valve body, 1/2 port size, Normal close, AC220V, DIN connection, Black cover, G thread, ERP code is: UW15E2

### Specifications

Model	UW10	UW15	UW20	UW25	UW35	UW40	UW50
Orifice ( mm )	16	16	20	25	35	40	50
CV	4.8	4.8	7.6	12	24	29	48
Pressure range ( MPa )	0~0.8			0~0.7			
Acting type	Step pilot						
Working medium	Air, water, light oil						
Working temperature (°C)	-5~80°C ( No freezing )						
Power	AC:33VA DC: 20W			AC:70VA DC: 40W			